

KRONE®

LSA-PLUS® Disconnection Module

Issue 2



10 Pair



8 pair

KRONE LSA-PLUS® Disconnection Module, for 8 or 10 pairs with disconnection facility. Line testing is possible in both directions.

Features:

- Based on genuine LSA-PLUS® connection technology
- Fits on all LSA-PLUS® back mount frames
- Suitable for use in all xDSL and ADSL 2+ circuits
- Flexible indoor and outdoor use
- Robust long term environmental stability
- Supports LSA-PLUS® series 2 accessories
- Overvoltage protection using 10 pair protection magazine
- Overvoltage & overcurrent protection using single pair protection (IPM)

Compliance

- Type Approved against TEC, MDF Spec. GR/CTN-01/04 May 2005

Specifications

Conductor diameter of connectable wires

2 wires per contact 0.40 to 0.63 mm
1 wire per contact 0.63 to 0.8 mm AWG 22 to AWG 26

Insulation diameter of connectable wires 0.7 to 1.6 mm

SPEC SHEET



www.adc.com/in • 1800 425 8232

KRONE®

LSA-PLUS® Disconnection Module

Properties

Connection frequency..... > 200 times
 Test access plug in cycles > 250

Electrical values

Contact resistance < 2.5 m ohms
 Insulation resistance > 50 000 Mega ohms
 Dielectric strength 2 KV rms
 Impulse current 5 kA (8/20 micro sec)
 Current carrying capacity 2 A

Environmental

Temperature operation.....- 5 C to +60 C
 Relative humidity95%, no water condensation, no ice

Materials

PlasticsPBT, resistant against aggressive chemicals (PVC softener)
 Plastics flammability class UL 94 V0
 Contact Special brass, silver plated

Ordering Information

Description	Quantity	Colour	Product No.
KRONE LSA-PLUS® Disconnection module 2/10	Each	White	6089 2 011-02D
KRONE LSA-PLUS® Disconnection module 2/10	Each	White/ Grey	6089 2 011-02
KRONE LSA-PLUS® Disconnection module 2/8	Each	White	6036 2 002-00D
KRONE LSA-PLUS® Disconnection module 2/8	Each	White/ Grey	6036 2 002-00

WARNING – KRONE* TYPE is NOT KRONE*. Occasionally customers may come across copies of KRONE* products being sold in the market which are being passed off as original KRONE* products. Using these products may affect the functionality and quality of your network. Ensure use of original products for an efficient network. Original KRONE products are sold ONLY through ADC authorised distributors.

SPEC SHEET

GENUINE
KRONE
 PRODUCTS

KRONE Communications Ltd is now as ADC India Communications Ltd.



www.adc.com/in

10C, II Phase Peenya Industrial Area
 Bangalore 560 058
 Sales Support: 1800 425 8232

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
 Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

6089 2 011-02DIN.dot / Issue 2 © 2010 ADC Telecommunications, Inc. All Rights Reserved.